

MATERIAL SAFETY DATA SHEET

This product is classified as a Non Hazardous Substance according to criteria of NOHSC Australia

1. IDENTIFICATION OF THE MATERIAL

Product Name: Aquacoat 510 SS Gloss Other Names; W60 Single Sided Gloss

Product Code: Aquacoat 510

Supplier: GSB Chemical Co. Pty. Ltd

GSB Chemical Co. Pty. Ltd Telephone: +61 03 9457 1125 ACN 004 355113 Facsimile: +61 03 9459 7978

84 Camp Road Internet: http://www.gsbchem.com.au Broadmeadows Vic. 3047 e-mail: info@gsbchem.com.au

Major Uses and Methods of Application: Aqueous emulsion coating used in the printing industry.

2. COMPOSITION

CAS No. PROPORTION

Mixture 1 – 10%

Mixture >60%

Mixture 10 – < 30%

Mixture 1 - < 10%

HAZARDS IDENTIFICATION

Risk Phrases: None allocated.

Aqueous Wax Dispersion

Long Chain Poly Glycol Compounds

Polymer Emulsions

Acrylic Resin Solution

Poisons Schedule: None allocated.

4. FIRST AID MEASURES

For advice, contact a Poisons information Centre (Phone Australia 13 1126, New Zealand 0 800 764766)

Swallowed: If swallowed, DO NOT induce vomiting. If conscious give 1 to 2 glasses of water to

drink. If irritation develops transport to doctor or hospital.

Eye: If in eyes, hold eyelids apart and flush the eye continuously with running water.

Continue flushing until advised to stop by the Poisons Information Centre or a

doctor, or for at least 15 minutes.

Skin: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair

with running water. Immediately transport to hospital or doctor.

Inhaled: Move victim to fresh air. Apply resuscitation if victim is not breathing - If trained

personnel available administer oxygen if breathing is difficult.

Advice to Doctor: Treat symptomatically.

First Aid Facilities:

Eye wash fountain, safety shower and normal wash room facilities

Product Name: Aquacoat 510

Issued: November 2009 Version 1.2 Page 1 of 4

FLAMMABILITY: This material is not a flammable or combustible liquid.

Fire/Explosion Hazard If safe to do so, move undamaged containers from fire area.

Suitable Extinguishing Media: Use extinguishing media suitable for surrounding fire situation.

Hazards From Combustion Products: Decomposes on heating emitting oxides of carbon, oxides of nitrogen and small quantities of noxious smoke.

Precautions for Fire Fighters

and Special Protective Equipment: Fire fighters to wear Self-contained breathing apparatus (SCBA) in confined

spaces, in oxygen deficient atmospheres or if exposed to products decomposition.

Full protective clothing is also recommended

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Low hazard product. If product spills onto floors it will represent a slip hazard, walk

cautiously. Wear protective equipment to prevent skin and eye contact, as outlined

under personal protection in this MSDS.

Methods and Materials for Containment and Clean

Up Procedures: Throw absorbent (diatomaceous earth or other inert material) on top of spill,

ALLOW TO ABSORB, then shovel up and seal in properly labeled container(s) for

disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling: Store away from energetic oxidizing agents and strong acids. For further

information please refer to the Engineering Controls of this MSDS.

Conditions for Safe Storage: Keep containers tightly closed, when not using this product. Store in a cool place

and out of direct sunlight. Store in original packages as approved by manufacturer.

8. EXPOSURE AND PERSONAL PROTECTION

No exposure standards are available for this product, however, the following exposure standards have been assigned by Worksafe Australia Exposure Standard [N0HSC] for components of the product

Personal Protection:

Eye protection: Safety glasses, goggles or face shield as required

Hand Protection: PVC, neoprene or nitrile rubber gloves

Footwear: Rubber boots

Respiratory Protection: If airborne concentrations are likely to exceed the Exposure Standard, wear approved

organic vapour respiratory protection (AS/NZS 1715 and 1716). In high vapour

concentrations, wear an air-supplied hood.

Safety showers with eyewash should be provided in all areas where product is handled. No respiratory protection

required if engineering, storage and handling controls are adequate,

Engineering Controls: General (mechanical) room ventilation plus special local exhaust ventilation at points

where vapour could escape to the work environment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White coloured liquid with a mild ammonia odour.

Boiling Point: Not available. Vapour Pressure: Negligible.

Product Name: Aquacoat 510

Issued: November 2009 Version 1.2 Page 2 of 4

Specific Gravity: Not available. Flash Point: Not available.

Flammability Limits: Not available. Solubility in Water: Miscible.

Other Properties

Evaporation Rate: Negligible.

Viscosity: Viscous

10. STABILITY AND REACTIVITY

Stable under normal conditions of use and storage. Ensure containers are kept closed when not in use.

CHEMICAL STABILITY: Stable under normal conditions of use.

CONDITIONS TO AVOID: High temperatures and mixing with incompatibles.

INCOMPATIBLE MATERIALS: Energetic oxidizing agents and strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Decomposes on heating emitting oxides of carbon, oxides of nitrogen and small

quantities of noxious smoke.

HAZARDOUS REACTIONS: Will not occur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected, if the product is handled in accordance with this Material Safety Data Sheet and the product label. Symptoms and effects that may arise if the product is mishandled and overexposure occurs are:

ACUTE HEALTH EFFECTS:

Swallowed: Swallowing large quantities may cause irritation to mouth, throat and stomach with

effects including pains in the stomach, which may lead to nausea and possible

diarrhoea.

Eye: May cause mild irritation to the eyes.
Skin: May cause mild irritation to the skin.
Inhaled: Mists from the product may cause irritation.

Chronic: Prolonged or repeated skin contact may lead led to drying/defatting of the skin and

potential dermatitis in some susceptible individuals.

12. ECOLOGICAL INFORMATION

Ecotoxity: Negligible ecotoxicity.

Mobility: Readily absorbed in the soil.

Persistence / Degradability: Biodegradable.

There is no other ecological information available for this product, however, large quantities should not be discharged into drains, sewers or waterways

13.DISPOSAL

Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Contact local authority

14. TRANSPORT INFORMATION

Product Name: Aquacoat 510

Issued: November 2009 Version 1.2 Page 3 of 4

Road Transport (ADR/RID), Air Transport (ICAO/IATA), Sea Transport (IMDG)

UN Number: None allocated Proper Shipping Name: NONE ALLOCATED

Dangerous Goods Class: None allocated Packing Group: None allocated.

15. REGULATORY INFORMATION

Risk Phrases: None allocated.

Safety Phrases: S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

Poison Schedule: None allocated

16. OTHER INFORMATION

Contact: Technical Manager

Telephone (03) 94571125

The information and recommendations in this publication are to the best of our knowledge accurate at the time of publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or process. Nothing herein is to be construed as warranty, expressed or implied. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular use.

END OF MSDS

Product Name: Aquacoat 510

Issued: November 2009 Version 1.2 Page 4 of 4